

Contrasts

Peter von Rohr

2023-03-27

Contrasts

- ▶ Linear combination of parameters
- ▶ In R used to determine which estimable functions are shown as factor level effects

Example Dataset

Table 1: Body Weight and Breed of Beef Cattle Animals

Animal	Body Weight	Breed
1	471	Angus
2	463	Angus
4	470	Angus
7	518	Limousin
8	511	Limousin
9	510	Limousin
10	541	Limousin
3	481	Simmental
5	496	Simmental
6	491	Simmental

Contrasts in R

```
(mat_ctr <- contrasts(as.factor(tbl_flem_bw_breed$Breed)))
```



```
##                 Limousin Simmental
## Angus             0             0
## Limousin          1             0
## Simmental         0             1
```

Model Matrix

```
model.matrix(lm(`Body Weight` ~ Breed,  
                 data = tbl_flem_bw_breed))
```

```
##      (Intercept) BreedLimousin BreedSimmental  
## 1            1              0                  0  
## 2            1              0                  0  
## 3            1              0                  0  
## 4            1              1                  0  
## 5            1              1                  0  
## 6            1              1                  0  
## 7            1              1                  0  
## 8            1              0                  1  
## 9            1              0                  1  
## 10           1              0                  1  
## attr(,"assign")  
## [1] 0 1 1  
## attr(,"contrasts")  
## attr(,"contrasts")$Breed
```

Estimable Functions

- ▶ extend contrasts matrix by one row of all ones for the intercept

```
##           (Intercept) Limousin Simmental
## Angus          1         0         0
## Limousin       1         1         0
## Simmental      1         0         1
```

Estimable Functions II

- ▶ Inverse of extended contrasts matrix

```
##           Angus Limousin Simmental
## (Intercept)     1         0         0
## Limousin       -1         1         0
## Simmental      -1         0         1
```

- ▶ First row: which group means are used for intercept
- ▶ Other rows: vectors q^T representing estimable functions

Validation

- ▶ Compute a solution of least squares normal equation
- ▶ Use matrix of estimable functions to validate effects estimates

Default Contrasts

- ▶ Per default: treatment contrasts
- ▶ Factor levels in alphabetical order
- ▶ First level corresponds to control, other levels are treatments
- ▶ Intercept estimate as mean observation for control group
- ▶ Effects estimates as difference between treatment and control solutions of normal equations

Other Contasts

- ▶ Helmert
- ▶ sum
- ▶ poly

Custom Contrasts

- ▶ Construct own matrix of estimable functions
- ▶ Invert that matrix
- ▶ Ignore first column
- ▶ Use remaining matrix of contrasts as argument in `lm()`