

# Genetic Evaluation - Solution 3

Peter von Rohr

2021-04-30

## Problem 1 Analysis of Variance

Estimate the variance component for the sire effect using an analysis of variance. The data is available from [https://charlotte-ngs.github.io/gelasmss2021/data/gel\\_sire\\_w10.csv](https://charlotte-ngs.github.io/gelasmss2021/data/gel_sire_w10.csv). Because the data contains just female animals, the fixed effect of the sex can no longer be estimated.

### Hint

- Use the functions `aov()` to do the analysis of variance and the function `summary()` on the ANOVA result to get the relevant parts of the variance components.

### Solution

The data is read using

```
s_data_sire <- "https://charlotte-ngs.github.io/gelasmss2021/data/gel_sire_w10.csv"
tbl_sire_aov <- readr::read_csv2(file = s_data_sire)

## i Using ',' as decimal and '.' as grouping mark. Use `read_delim()` for more control.

##
## -- Column specification -----
## cols(
##   Id = col_double(),
##   slh = col_double(),
##   hrd = col_double(),
##   age = col_double(),
##   cw = col_double(),
##   sire = col_double()
## )

tbl_sire_aov$slh <- as.factor(tbl_sire_aov$slh)
tbl_sire_aov$hrd <- as.factor(tbl_sire_aov$hrd)
tbl_sire_aov$sire <- as.factor(tbl_sire_aov$sire)
# anova
aov_sire <- aov(cw ~ slh + hrd + age + sire, data = tbl_sire_aov)
(summary_aov_sire <- summary(aov_sire))

##          Df  Sum Sq Mean Sq F value Pr(>F)
## slh        2  141381   70690   783.9 <2e-16 ***
## hrd        4  1880642   470160   5213.5 <2e-16 ***
## age        1    24152    24152   267.8 <2e-16 ***
## sire       9    10387    1154     12.8 <2e-16 ***
```

```

## Residuals   1699  153217      90
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

From the Mean Sq of the residuals and of the sires, the estimates of the variance components can be computed.

The estimate  $\hat{\sigma}_e^2$  corresponds to the mean sum of squares for the residuals. Hence

$$\hat{\sigma}_e^2 = 90$$

The estimate of the sire variance  $\hat{\sigma}_s^2$  is computed as

$$\hat{\sigma}_s^2 = \frac{\text{Mean Sq(sire)} - \hat{\sigma}_e^2}{k}$$

where  $k = \frac{1}{r-1} \left[ N - \frac{\sum_{i=1}^r n_i^2}{N} \right]$  with  $r$  is the number of sires,  $N$  the total number of observations and  $n_i$  the number of progeny for sire  $i$ . To compute the value  $k$ , we need the progeny counts for each sire.

sire	prog_count
1	174
2	189
3	171
4	190
5	176
6	172
7	175
8	160
9	161
10	148

From the above table, we get

$$k = \frac{1}{r-1} \left[ N - \frac{\sum_{i=1}^r n_i^2}{N} \right] = 1/(10-1) \left[ 1716 - \frac{2.95948 \times 10^5}{1716} \right] = 171.5$$

```

n_msqsire <- summary_aov_sire[[1]]$`Mean Sq`[4]
n_hat sigmas2 <- (n_msqsire - n_hat sigmae2) / n_k

```

Putting everything together, we get

$$\hat{\sigma}_s^2 = \frac{1154 - 90}{171.5} = 6.2$$

From the estimate of the sire variance, we get the estimate of the genetic variance by multiplying it with four. Hence

$$\hat{\sigma}_a^2 = 4 * \hat{\sigma}_s^2 = 4 * 6.2 = 24.8$$

## Problem 2: Variance Components Estimation Using REML

Use the same data set as for Problem 1 and a sire model to estimate the same sire variance  $\sigma_s^2$ . The sire model is the linear mixed effects model that contains sire effects as random component. The model can be specified as

$$y = Xb + Zs + e$$

where  $y$  is the vector of observations,  $b$  is the vector of fixed effects which are the same as in Problem 1,  $s$  is the vector of random sire effects and  $e$  is the vector of random error terms.

### Hint

- Use the package `pedigreemm` to get a REML estimate for the sire variance component  $\sigma_s^2$ .
- We assume that the sires are not related. Hence variance-covariance matrix  $var(s)$  of the sire components are  $var(s) = I * \sigma_s^2$ .

### Solution

As the first step, we have to specify a pedigree. The sires are unrelated hence the corresponding pedigree corresponds to

```
ped_sire <- pedigree::pedigree(sire = rep(NA, n_nr_sire),
                                dam = rep(NA, n_nr_sire),
                                label = c(1:n_nr_sire))
```

The specified pedigree is used for the linear mixed effects model

```
require(pedigreemm)
lmem_sire <- pedigreemm(cw ~ slh + hrd + age + (1|sire),
                         pedigree = list(sire = ped_sire),
                         data = tbl_sire_aov)
summary(lmem_sire)

## Linear mixed model fit by REML ['lmerpedigreemm']
## Formula: cw ~ slh + hrd + age + (1 | sire)
##   Data: tbl_sire_aov
##
## REML criterion at convergence: 12610.8
##
## Scaled residuals:
##       Min     1Q   Median     3Q    Max 
## -3.2011 -0.6731  0.0137  0.6539  3.4813 
##
## Random effects:
##   Groups   Name        Variance Std.Dev.
##   sire     (Intercept) 6.257    2.501  
##   Residual           90.181   9.496  
##   Number of obs: 1716, groups: sire, 10
##
## Fixed effects:
##             Estimate Std. Error t value
## (Intercept) -77.17270  16.67579 -4.628 
## slh2         22.36751   0.56484 39.600
```

```

## slh3      4.27798   0.56818   7.529
## hrd2     88.81545   0.73294 121.176
## hrd3      9.28428   0.72408 12.822
## hrd4     58.98147   0.71719 82.239
## hrd5     20.36389   0.72889 27.938
## age       0.68269   0.04161 16.405
##
## Correlation of Fixed Effects:
##          (Intr) slh2   slh3   hrd2   hrd3   hrd4   hrd5
## slh2 -0.011
## slh3 -0.072  0.513
## hrd2 -0.018  0.014 -0.023
## hrd3 -0.012 -0.001 -0.003  0.493
## hrd4  0.009 -0.008 -0.025  0.497  0.501
## hrd5  0.004  0.010 -0.028  0.490  0.495  0.500
## age  -0.998 -0.007  0.056 -0.004 -0.009 -0.031 -0.026

```

### Problem 3: Variance Components Estimation Using an Animal Model

We are given the dataset with the response variable `carcass weight` (CW) and the predictor variables that resulted from the model selection process from Exercise 1. These consisted of

- sex (`sex`)
- slaughterhouse (`slh`)
- herd (`hrd`)
- age at slaughter (`age`)

The data is available from [https://charlotte-ngs.github.io/gelasmss2021/data/gel\\_bp\\_w10.csv](https://charlotte-ngs.github.io/gelasmss2021/data/gel_bp_w10.csv).

We use a mixed linear effects model to estimate the variance components for the random effects in the model.

$$y = Xb + Za + e \quad (1)$$

where  $y$  is a vector of observations,  $b$  is a vector of fixed effects found to be relevant in Exercise 1,  $a$  is a vector of random breeding values and  $e$  is a vector of random errors.

#### Hint

- Use the package `pedigreemm` to get an estimate of the variance components

#### Your Task

- Estimate the variance components  $\sigma_a^2$  and  $\sigma_e^2$  for the two random component  $a$  and  $e$ , respectively.

#### Solution

We first have to read the data

```
s_data_path_gel_ex2 <- "https://charlotte-ngs.github.io/gelasmss2021/data/gel_bp_w10.csv"
tbl_gel_ex2 <- readr::read_csv2(file = s_data_path_gel_ex2)
```

```
## i Using ',' as decimal and '.' as grouping mark. Use `read_delim()` for more control.
```

```

## 
## -- Column specification -----
## cols(
##   Id = col_double(),
##   sex = col_double(),
##   slh = col_double(),
##   hrd = col_double(),
##   age = col_double(),
##   cw = col_double(),
##   sire = col_double(),
##   dam = col_double()
## )
colnames(tbl_gel_ex2);dim(tbl_gel_ex2)

## [1] "Id"    "sex"   "slh"   "hrd"   "age"   "cw"    "sire"  "dam"
## [1] 5325     8

```

The fixed effects are converted into factors

```

tbl_gel_ex2$sex <- as.factor(tbl_gel_ex2$sex)
tbl_gel_ex2$slh <- as.factor(tbl_gel_ex2$slh)
tbl_gel_ex2$hrd <- as.factor(tbl_gel_ex2$hrd)

```

From the help file of `pedigreemm`, we can see that we first have to define a pedigree.

```

ped <- pedigreemm::pedigree(sire  = tbl_gel_ex2$sire,
                             dam   = tbl_gel_ex2$dam,
                             label = tbl_gel_ex2$Id)

```

Now the model can be specified as for the other functions to fit linear mixed effects model, such as `lmer`.

```

# This takes more than one hour to run.
require(pedigreemm)
# according to https://stat.ethz.ch/pipermail/r-sig-mixed-models/2014q1/021609.html
options(lmerControl=list(check.nobs.vs.nlev="ignore",
                         check.nobs.vs.rankZ = "ignore",
                         check.nobs.vs.nRE="ignore"))
s_lmem_file <- "lmem_gel_ex2.rds"
if (file.exists(s_lmем_file)){
  load(file = s_lmем_file)
} else {
  lmem_gel_ex2 <- pedigreemm(cw ~ sex + slh + hrd + age + (1|Id),
                               data = tbl_gel_ex2,
                               pedigree = list(Id = ped))
  saveRDS(lmem_gel_ex2, file = s_lmем_file)
}
summary(lmem_gel_ex2)

```